Torque wrenches

Product information
- with ratchet
- torque range 1…200 Nm; with automatic short distance release; can be heard, seen and felt when the set value is reached. Release accuracy ± 4% of the scale value.
- type “D” is pre-set to 10 Nm suitable for our HPC chucks Series no. 4300, 4301, 4243, 4244





				type A	type D	type E	type B	type C
			Series no.	**4915**	**4987**	**4988**	**4989**	
type	drive	L mm	torque Nm	**EDP Number**	**EDP Number**	**EDP Number**	**EDP Number**	
A	1/4“	–	0.4-1	**9049150010010**				
A	1/4“	142	0.5-2	**9049150020000**				
A	1/4“	–	1.5-3	**9049150030000***				
A	1/4“	160	0.8-5	**9049150050010**				
A	1/4“	–	2.0-7	**9049150080000**				
D	1/4“	–	10		**9049870100000**			
E	1/4“	–	0.4-14			**9049880140000**		
B	3/8“	390	10-50				**9049890500000**	
C	1/2“	514	40-200				**9049892000000**	

*Includes 4mm hex wrench

Socket/attachments

Product information
- for hexagon socket screws
- Type D for HPC clamping chuck





Type A: 1/4“-hexagon drive
Type B: 3/8“-square drive
Type C: 1/2“-square drive
Type D: 1/4“-square drive

				Series no.	**4916**
SW	drive	L mm	torque wrenches type		**EDP Number**
2	1/4“	50	A		**9049160020190**
2.5	1/4“	50	A		**9049160025240**
3	1/4“	50	A		**9049160030300**
3	3/8“	52	B		**9049160030380**
4	1/4“	55	D		**9049160040000**
4	3/8“	100	B		**9049160040380**
5	3/8“	100	B		**9049160050480**
6	3/8“	100	B		**9049160060600**
8	3/8“	100	B		**9049160080750**
6	1/2“	120	C		**9049160060380**
8	1/2“	120	C		**9049160080480**
10	1/2“	140	C		**9049160100600**
12	1/2“	140	C		**9049160120000**